



HM-BT-BAT-ER

Bluetooth HART Modem, Battery Powered

**Description:**

Perform HART communications between a HART transmitter and a Windows or an Android device using Bluetooth.

Features and Benefits:

- Access hard to reach HART instrumentation from the ground or from your truck
- Improves plant personnel safety and productivity
- Easy HART instrument configuration using PC's or Mobile devices without wires
- Less clutter on desk or workbench
- Reliable wireless communication up to 275 ft (83.8m)
- Internal antenna
- Rechargeable Li-Ion battery via mini-USB connector
- Integral heavy duty HART Mini-grabber connectors
- Meets HART Physical Layer Spec HCF_SPEC-54
- High security 128 bit encryption
- Rugged ABS plastic enclosure with rubber boot
- Integrated loop for hanging strap attachment
- Works with DevCom2000 and DevComDroid and other HART software
- 1 Year warranty



Specifications:

Enclosure

Material	High strength ABS Plastic
Boot	Black Silicone 60
Dimensions	2.00" x 2.75" x 0.80" (50mm x 70mm x 20mm)
Total Unit Weight	4.8 oz (136 g)

Cables

HART Cable Length	4' (1.2 m)
HART Cable Connectors	Mini-Grabber

HART

Interface	Capacitive coupling
Output	600 mVpp
Leakage	< 10 uA
Connections	Across loop resistor or HART field device
Specifications	HART 4, HART 5, HART 6, HART 7, <i>wirelessHART</i> HART Physical Layer Spec HCF_SPEC-54

Computer

Operating System	Windows 7 and higher Android 4.3 and higher
------------------	--

Bluetooth

Specifications	Bluetooth v2.0
Frequency	2.4 GHz
Class 1 Master Distance	275' (83.8m)
Class 2 Master Distance	25' (7.6m)

Battery

Type	Rechargeable Li-Ion
Life	19 hours continuous use

Environmental

Operating Temperature	0 degC to 50 degC (32 degF to 122 degF)
Storage Temperature	-40 degC to 85 degC (-40 degF to 185 degF)
Humidity	0% to 99% (non-condensing)

Compliances

CE Certification	EN 61326 (EMC), Directive 2011/65/EU (RoHS)
------------------	---

ProComSol, Ltd

Process Communications Solutions

Phone: 216.221.1550
Toll Free: 877.221.1551
Email: sales@procomsol.com
Web: www.procomsol.com